

## FormsPro 4000se Series

Set It and Forget It Forms Printing



FormsPro 4000se Series printers can solve your toughest printing problems and automate most paper handling functions. With the FormsPro 4300se, 4500se or 4503se, you'll print with greater legibility and unsurpassed reliability. The FormsPro 4000se Series printers include:

### Tractor System

The FormsPro 4300se and 4500se have a single set of straight-up tractors. The FormsPro 4503se has the Tri-Trak system with three sets of straight-through tractors.

### High-Speed for High-Volume Printing

With a draft speed up to 530 cps, FormsPro printers can print a typical 1,000 character document in less than five seconds. That's over 700 documents per hour!

### Waste-Free Forms Tear-Off

After you tear off a form, the next is automatically positioned for printing.

### Superior Legibility — Even on 9-Part Forms

Auto-Gap feature adjusts the print-head according to form thickness.

### Trouble-Free Forms Handling

Easy-Load tilt-up top simplifies loading. Straight-up paper path eliminates forms buckling and jamming. Paper jam sensor permits reliable, unattended operation.

### Automatic Page Edge Sensor

Optical sensor prevents printhead from printing beyond the edges of the loaded form.

### Stores Parameters for Up to 10 Forms

Spacing, margins, font and 11 other parameters are set using four front panel buttons. Options are displayed on a 2 x 16 LCD display. Once you've set the parameters for a form, they can be stored and recalled at any time.

### Ruggedly Built for Reliable Operation

FormsPro printers are designed to withstand 100% duty cycles. The printhead carries a two-year limited warranty when used in combination with a Printek brand ribbon — longer than any printhead in the industry. A one year warranty is offered if a Printek brand ribbon is not used.



Call today for a no-obligation demonstration 1.888.211.3400

# FormsPro 4000se Series



## Other Features

Options and accessories include: Coax, Twinax, TN5250, IPDS, Ethernet, and wireless 802.11b, FormsCutter, printstand, and Imager and ImagerPlus bar code support.



An optional printstand features a paper guide which helps steer long reports into the rear catch basket.



The 4503se's unique Tri-Trak paper handling system keeps three forms loaded at all times.

Printek and the Printek logo are registered trademarks of Printek, Inc. Centronics is a trademark of Centronics Data Computer Corp. DEC is a registered trademark of Digital Equipment Corp. Epson is a registered trademark of Seiko Epson Corp. FX is a registered trademark of Epson America, Inc. IBM is a trademark of International Business Machines.



## Specifications

Print Modes	4500se/4503se	4300se
Fast Draft	530 cps	300 cps
Draft	400 cps	225 cps
Fast Draft/High Impact	265 cps	150 cps
High Impact	200 cps	110 cps
Letter Quality	100 cps	55 cps
Optical Quality	65 cps	38 cps
Graphics*	15,360 dps	8,640 dps

## Character Matrix

**Fast Draft:** 9 x 9 cell  
**Draft:** 12 x 9 cell  
**Letter Quality:** 24 x 18 cell  
**Optical Quality:** 36 x 18 cell

## Printhead

18 wire parallel array.

## Character Sets

Fast Draft, Draft and Letter Quality for Epson and IBM Proprinter. Optical Quality for OCR-A and OCR-B.

## Character Spacing

5, 6, 6.7, 7.5, 8.4, 8.6, 10, 12, 13.3, 15, 16.7, 17.1 and 20 cpi.

## Line Length

13.6 inches (34.5 cm).

## Line Spacing

6 and 8 lpi. Also software programmable.

## Paper Handling

**Tear Bar:** Auto-Scroll allows zero tear-off distance.  
**Auto-Gap:** Adjusts printhead to form thickness.  
**Paper Type:** Fanfold, continuous forms, edge punched, 15 lb. minimum weight for single-part paper.  
**Sensing:** Paper motion, paper edge and paper out.

## Special Features

Horizontal print fine adjustment. Ability to name forms (i.e. "Invoice") for operator display.

## Operator Controls

**Normal Operating Mode:** Online, Form Feed/Load, Form Select/Unload and Vertical Print Adjustment.

## Form Parameters

Non-volatile memory for ten forms, each supporting settings for: tractor path, cpi, lpi, form length, left and right margins, top and bottom margins, unidirectional printing, slashed or non-slashed zero, language, font, high-impact on/off.

## Operator Indicators

LEDs for Power, Online and Fault; 2 x 16 LCD for form selection; on/off line status and error descriptions.

## Ribbon

**Cartridge:** nylon fabric, mobius loop, 23 million characters.

## Power Requirements

**Voltage:** 110-230 VAC  $\pm 10\%$   
**Frequency:** 50-60 Hz  
**Power Consumption:** 60W non-printing, 225W printing.

## Paper Slew Rate

12 ips, with slower rates user selectable for difficult forms.

## Paper Width

2.5" to 15" (6.4 cm to 38.1 cm).

## Paper Loading

Straight path, bottom loading.

## Multi-part Forms

1 to 9 parts; 0.025" max. thickness.

## Graphics Density\*

60 to 240 dpi horizontally x 72 dpi vertically.

## Audible Noise (Draft Mode)

62 dBA.

## Setup (Automatic Methods)

Control panel, pluggable cloning module or remote download via Windows program.

## I/O Buffer

32k

## Standard Interfaces

**Parallel:** Centronics compatible.  
**Serial:** RS232, 300 to 9,600 baud.

## Optional Interfaces

Coax, Twinax, TN5250, IPDS, Ethernet, and wireless 802.11b.

## Software Controls

Emulation choice of Printek, Epson FX, IBM Proprinter, DEC LA120/LA210, Genicom ANSI or Basic Bar Codes (Includes Code 39, 2 of 5, Interleaved 2 of 5, more available through Genicom emulation).

## Physical Specifications

**H x W x D:** 9.5" x 25" x 20.3"  
 (24 cm x 63.5 cm x 51.5 cm)  
**Weight:** 43 lbs. (19.5 kg)

## Reliability

**MTBF:** 10,000 hours on electronics with no duty cycle limitations.  
**Printhead Life:** 500 million draft equivalent characters.  
**Warranty (Return to Depot):** One-year printer warranty, two-year limited printhead warranty when Printek brand ribbons are used; one-year warranty when non-Printek brand ribbons are used.

\*May be emulation dependent.